HANFORD TANK WASTE TREATMENT AND

IMMOBILIZATION PLANT



BIDDER REQUEST FOR INTEREST & PRE-QUALIFICATION PACKAGE

OFFICIAL USE ONLY (when completed)

May be exempt from public release under the Freedom of Information Act (5 U.S.C. 552), exemption number and category: 4.

Commercial/Proprietary

Department of Energy Review required before public release

Name/Org: Jose Velasquez/ P&S Date: 12/28/2023

Guidance (if applicable): N/A

Requisition No. 24590-CM-MRA-ESM0-00002

HLW Switchgear Pre-Fabricated Electrical Powerhouse

COMPANY NAME:	
---------------	--



1.0 Introduction

Bechtel National Inc., herein referred to as Contractor, intends to issue a Request for Proposal (RFP) for a **Plant Equipment** Purchase Order for the Hanford Waste Treatment and Immobilization Plant (WTP) project in Richland, WA. Companies must be <u>pre-qualified</u> by Contractor to be included on the bid list. To support the pre-qualification evaluation process, the prime potential bidder (1st tier subcontractor) must provide the requested information and respond to questions within this document. The Experience Statement should include relevant information for both the prime bidder and any planned lower-tier supplier or subcontractor. Additional supporting documentation such as brochures and company profiles may also be submitted.

*Please note that additional supporting documentation will be required as part of the formal RFP process.

2.0 Project Description and Location

The Hanford Tank Waste Treatment and Immobilization Plant (WTP) is a complex of radioactive waste treatment processing facilities designed and constructed by Bechtel National, Inc. for the Department of Energy (DOE). The facility will process the Hanford Site tank waste and convert the waste into a stable glass form.

The Project site is located in the 200 East Area of the Hanford Reservation near Richland, Washington, along the Columbia River. The site elevation varies from 662 to 684 feet above mean sea level. Ambient temperature range is -23 degrees F minimum to 113 degrees F maximum, with relative humidity of 5% minimum to 100% maximum. The project design life is 40 years.

Information about the WTP Project can be found on http://www.hanfordvitplant.com.

3.0 Scope of Work

Award Type: FIRM FIXED PRICE with Economic Price Adjustment

Estimated RFP Date: March 2026

A complete manufacturer's standard 1 (one) prefabricated metal or concrete building, shall include the following:

Entire freestanding superstructure, including exterior envelope and complete interior work with finishing, self-framing insulated metal roof, siding, wall panels, doors, louvers, accessories, painting, penetrations, and penetration seals associated with the design

Complete floor design supported on piers raised 7 ft. (minimum) above grade including floor penetrations as required for cable and water (pre-action fire suppression system and eye wash) entry from below and floor drains.

Designing, furnishing, installation, and testing of lighting (interior, exterior, and emergency egress) system, convenience receptacles, HVAC system, fire detection alarm and suppression system, lightning protection system, and grounding system.

The building shall be seismically designed in accordance with the requirements of applicable building codes to survive the maximum design earthquake of the seismic zone specified.

Equipment specified below shall be inspected and tested by the original equipment manufacturers in accordance with manufacturer's procedures.



Perform inspections and functional tests for building services, such as HVAC system, lighting, receptacles, BMS, and alarming system, etc.

Perform insulation resistance (megger) tests on each load center, switchgear, and panelboards bus sections, phase to phase and phase to ground using manufacturer's instructions.

Perform continuity tests on any cables and bus bar joints assembled in Seller's facility.

For all power cables installed by Seller, the following shall be performed:

- 100 percent point to point continuity check/test
- Insulation resistance (megger) tests
- Verify all bolted electrical connections within shipping limitations are torqued per manufacturer's specifications.

Fire Detection and Alarm System Testing Requirements

- After installing wiring devices, Seller shall perform tests for ground faults, stray voltage, short circuit faults, loop resistance, circuit integrity per NFPA 72 and compliance with the equipment manufacturer's requirements
- Stray Voltage
- Loop Resistance

Prior to shipment, Seller shall perform an overall field evaluation (FE) by a Recognized NRTL, to perform a NEC compliance inspection for B34, Switchgear Building. The FE report shall be submitted to Buyer for review and approval. Buyer representative will perform an independent field evaluation against applicable UL standards, and NEC compliance inspection at Seller's facility

Equipment and Materials Required

- Two (2) 13.8kV Type 2C arc-resistant switchgear line-ups, each consisting of A and B assemblies (MVE-SWGR-34001/2-A and MVE-SWGR-34001/2B), tied together via cables between tie breakers, with main and tie breakers interlocked to prevent extended paralleling of buses
- One (1) Uninterruptible Power Supply System (rectifier, inverter, mainetannace bypass switch, bypass source transformer, battery bank, battery monitor,
- One (1) 125V DC system to provide control power to the medium voltage switchgear. System shall
 consist of batteries, battery chargers, and distribution panel boards
- One (1) 480V 208/120V Distribution Transformer and Distribution Panelboard
- Two (2) 480V Distribution Panelboards
- Design and installation of raceway system for both Buyer and Seller installed power, control and instrument cables, and communication/data cables
- Hydrogen mitigation system
- Design, Procurement, Fabrication, Mounting, installation, and testing for Controller Cabinet
- Furnishing, installation, and testing of fire protection water system (FPW) in accordance with NFPA 13
 requirements and this specification. Preaction Fire Suppression System. Pre-action valve and
 compressor to be located in under-building heated doghouse.
- Furnishing, installation, and testing of fire detection and alarm system (FDE)
- Multipurpose (Type A/B/C), dry chemical fire extinguishers in quantity and location(s) required to meet the NFPA 10, Standard for Portable Fire Extinguishers
- Instant water heater for

evewash station

COMPANY NAME:	
---------------	--



- Grounding System
- Lightning Protection System Design
- Communications Electrical System (CME)
- HVAC System (cooling units included)
- Cable tray and conduit system
- Supplemental Factory Acceptance Tests (FAT)
- Seller is directed to procure the UPS system equipment from GUTOR (Schneider Electric), equipment Switchgear, 125VDC system, panel borads and transformers from EATON corporation, battery monitoring system from Eagle Eye Power Solutions, and pager system from RACO (Remote Alarms and Controls)

Codes

Switchgear Building

•	10 CFR 851	Worker Safety and Health Program.
•	10 01 11 03 1	Worker dalety and ricaliti regiant.

Occupational Safety and Health Standards. Code of Federal Regulations, as 29 CFR 1910

amended.

ANSI/AISC 360 Specification for Structural Steel Building

Power Cable Ampacities ICEA/NEMA

AISI S100 North American Specification for the Design of Cold-Formed Steel Structural

Members

ANSI/ASHRAE 15 Safety Standard for Mechanical Refrigeration Systems

American National Standard for Product Safety Signs and Labels ANSI/NEMA Z535.4

ASCE 7, 2022 Minimum Design Loads and Associated Criteria for Buildings and Other

Structures

ASHRAE 52.2 Methods of Testing General Ventilation Air-Cleaning Devices for Removal

Efficiency by Particulate Size

ASHRAE 62 Ventilation for Acceptable Indoor Air Quality

Energy Standard for Buildings except Low-Rise Residential Buildings ASHRAE 90.1, 2022 Handbooks Fundamentals, Applications, Refrigeration, Systems and **ASHRAE**

Equipment

Standard Specification for General Requirements for Flat-Rolled Stainless and ASTM A480 Heat-Resisting Steel Plate, Sheet, and Strip

ASTM C665 Standard Specification for Mineral-Fiber Blanket Thermal Insulation for Light Frame Construction and Manufactured Housing

ASTM C719 Standard Test Method for Adhesion and Cohesion of Elastomeric Joint Sealants under Cyclic Movement (Hockman Cycle)

ASTM C834 Standard Specification for Latex Sealants

Standard Specification for Elastomeric Joint Sealants ASTM C920

ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials Standard Test Method for Behavior of Materials in a Vertical Tube Furnace at ASTM E136 750°C

AWS D1.1/D1.1M Structural Welding Code - Steel Structural Welding Code - Sheet Steel AWS D1.3/D1.3M

FM 5-11 Lightning and Surge Protection for Electrical Systems

FM 5-18 Protection of Electrical Equipment Single Phasing and Related Faults

Switchgear and Circuit Breakers FM 5-19

Cables and Bus Bars FM 5-31



IBC, 2021 International Building Code
 IFC, 2021 International Fire Code

IEEE/ANSI-C2 National Electric Safety Code (NESC)

IEEE 142
 Recommended Practice for Grounding of Industrial and Commercial Power

System

 IEEE 242 Recommended Practice for Protection and Coordination of Industrial and Commercial Power Systems

 IEEE 260.1 American National Standard Letter Symbols for Units of Measurement (SI Units, Customary Inch-Pound Units, and Certain Other Units)

• IEEE 315 Graphic Symbols for Electrical and Electronics Diagrams

IEEE 399 Recommended Practice for Industrial and Commercial Power Systems Analysis
 IEEE 493 Recommended Practice for the Design of Reliable Industrial and Commercial

Power Stations

• IEEE 519 Recommended Practices and Requirements for Harmonic Control in Electrical

Power Systems

• IEEE 1100 Recommended Practice for Powering and Grounding for Sensitive Electronic

Equipment

 IEEE 1187 Recommended Practice for the Installation Design and Installation of Valve-Regulated Lead-Acid Storage Batteries for Stationary Applications

 IEEE 1202 Standard for Flame Testing of Cables for Use in Cable Tray in Industrial and Commercial Occupancies

IES Lighting Handbook Reference & Application

 IESNA/ANSI RP-7 Recommended Practice for Lighting Industrial Facilities MBMA Metal Building Systems Manual

NEMA 250 Enclosures for Electrical Equipment (1000 Volts Maximum)

NEMA ICS 6 Industrial Control and Systems: Enclosures

NEMA VE 1 Metal Cable Tray Systems

NEMA VE 2 Cable Tray Installation Guidelines

NEMA WC 70 Power Cables Rated 2000V or Less for the Distribution of Electrical Energy

NFPA 10, 2022 Standard for Portable Fire Extinguishers

NFPA 13, 2022 Standard for the Installation of Sprinkler Systems

NFPA 70, 2023 National Electrical Code (NEC)

NFPA 70E, 2015 Standard for Electrical Safety in the Workplace

NFPA 72, 2022 National Fire Alarm and Signaling Code

NFPA 80, 2022 Standard for Fire Doors and Other Fire Windows

NFPA 90A, 2021
 Standard for the Installation of Air-Conditioning and Ventilation SystStandards

NFPA 101, 2021 Life Safety Code

NFPA 780, 2023 Standard for the Installation of Lightning Protection Systems
 UL 44 Standard for Safety Thermoset-Insulated Wires and Cables

UL 96 Safety Lightning Protection Components

UL 96A Safety Installation Requirements for Lightning Protection Systems

UL 467 Standard for Safety Grounding and Bonding Equipment

UL 508A Standard for Safety Industrial Control Panels

• UL 1277 Standard for Safety Electrical Power and Control Tray Cables with Optional

Optical-Fiber Members

UL 1581 Safety Reference Standard for Electrical Wires, Cables, and Flexible Cords

COMPANY NAME:	
---------------	--



13.8kV Switchgear

•	ANSI C37.55	Metal-Clad Switchgear Assemblies Conformance Test Procedures
•	IEEE C37.04	Standard Rating Structure for AC High-Voltage Circuit Breakers

• IEEE C37.06 Standard for AC High-Voltage Circuit Breakers Rated on a Symmetrical Current

Basis – Preferred Ratings and Related Required Capabilities for Voltages over 1000 Volts

 IEEE C37.09 Standard Test Procedure for AC High-Voltage Circuit Breakers Rated on a Symmetrical Current Basis

IEEE C37.20.2 Metal-Clad Switchgear

• IEEE C37.20.7 Guide for Testing Metal-Enclosed Switchgear Rated up to 38 kV for Internal Arcing Faults

IEEE C37.90 Relays and Relay Systems Associated with Electric Power Apparatus

• IEEE C37.100.1 Standard of Common Requirements for High Voltage Power Switchgear Rated

Above 1000 Volts

IEEE C57.13 Requirements for Instrument Transformers

NEMA LA –1 Surge Arresters

NEMA SG-4 Alternating-Current High-Voltage Circuit Breakers

NEMA SG-6 Power Switching Equipment

• UL 467 Grounding and Bonding Equipment

UL 869A Safety Reference Standard for Service Equipment

Uninterruptible Power Supply (UPS) Systems

- CSA C22.2 No. 66.1/ Low Voltage Transformers Part 1: General Requirements UL 5085-1
- CSA C22.2 No. 66.2/ Low Voltage Transformers Part 2: General Purpose Transformers UL 5085-2
- IEC 62040-3 Uninterruptible Power Systems (UPS) Part 3: Method of Specifying the Performance and Test Requirements

IEEE 485
 Recommended Practice for Sizing Lead-Acid Batteries for Stationary

Applications

• IEEE 1184 Guide for Batteries for Uninterruptible Power Systems

 IEEE 1187 Recommended Practice for the Installation Design and Installation of Valve-Regulated Lead-Acid Storage Batteries for Stationary Applications

 IEEE 1188 IEEE Recommended Practice for Maintenance, Testing, and Replacement of Valve-Regulated Lead-Acid (VRLA) Batteries for Stationary Applications

 IEEE 1189 Guide for Selection of Valve-Regulated Lead-Acid (VRLA) Batteries for Stationary Applications

IEEE 1491 Guide for Selection and Use of Battery Monitoring Equipment in Stationary

Applications

NEMA 250 Enclosures for Electrical Equipment (1000 Volts Maximum)

NEMA PE1 Uninterruptible Power Supplies
 NEMA PE 5 Utility Type Battery Chargers

UL 94 Standard for Safety Test for Flammability of Plastic Materials for Parts in

Devices and Appliances

UL 1778 Standard for Safety - Uninterruptible Power Systems



125 Vdc System

IEEE 485 Recommended Practice for Sizing Lead Acid Batteries for Stationary

Applications

IEEE 946 Recommended Practice for the Design of DC Auxiliary Power Systems for

Generating Stations

• IEEE 1187 Recommended Practice for Installation Design and Installation of Valve –

Regulated Lead-Acid (VRLA) Storage Batteries for Stationary Applications

IEEE 1188 Recommended Practice for Maintenance, Testing and Replacement of Valve-

Regulated Lead-Acid Storage Batteries for Stationary Applications

IEEE 1189 Guide for Selection of Valve-Regulated Lead-Acid Storage Batteries for

Stationary Applications

NEMA 250 Enclosure for Electrical Equipment

NEMA CC 1 Electric Power Connection for Substations

NEMA PB 1 Panelboards

NEMA PE 5 Electromagnetic Interference (EMI)

IBC, 2021 International Building Code
 AWS D1.1 Structural Welding Code – Steel

Panelboards and Dry Type Transformers

NEMA PB1 Panelboards

NEMA ST 20 Dry-Type Transformers for General Applications

NEMA 250 Enclosures for Electrical Equipment (1000 Volts Maximum)
 UL 50 UL Standard for Safety Enclosures for Electrical Equipment

UL 67 UL Standard for Safety Panelboards

UL 94 Standard for Safety Test for Flammability of Plastic Materials for Parts in

Devices and Appliances

UL 1561 UL Standard for Safety Dry-Type General Purpose and Power Transformers –

Third Edition

Preaction Fire Suppression System

 ASTM A53 Standard Specification for Pipe, Steel, Black and Hot-Dipped, Zinccoated, Welded and Seamless.

 ASTM A182 Standard Specification for Forged or Rolled Alloy and Stainless-SteelPipe Flanges, Forged Fittings, and Valves and Parts for High Temperature Service.

 ASTM A312/A312M Standard Specification for Seamless, Welded, and Heavily Cold Worked Austenitic Stainless-Steel Pipes.

ASTM A403/A403M Standard Specification for Wrought Austenitic Stainless Steel Pipe Fittings.

 ASTM A705/A705M

 Standard Specification for Wrought Austenitic Stainless Steel Pipe Fittings.

ASTM A795/A795M Standard Specification for Black and Hot-Dipped Zinc-Coated (Galvanized) Welded and Seamless Steel Pipe for Fire Protection Use.

ASME B16.3 Malleable Iron Threaded Fittings: Classes 150 and 300.
 ASME B16.4 Gray Iron Threaded Fittings: Classes 125 and 250.

• ASME B16.5 Pipe Flanges and Flanged Fittings: NPS 1/2 Through NPS 24 Metric/Inch

Standard.

ASME B16.42 Ductile Iron Pipe Flanges and Flanged Fittings: Classes 150 and 300.
 AWS B2.1/B2.1M Specification for Welding Procedure and Performance Qualification

COMPANY NAME:	
---------------	--



- IBC (2021) International Building Code (IFC).
 IFC (2021) International Fire Code (IFC).
- FM Approval Guide.
- FM Data Sheet 2-8 (2017), Earthquake Protection for Water-Based Protection Systems
- Washington Administrative Code (WAC) Chapter 212-80 Fire Protection Sprinkler System Contractors.

Fire Detection and Alarm System

- Factory Mutual (FM) FM Fire Protection Approval Guide
- Factory Mutual Data Sheet 5-40, Fire Alarm Systems, Sept. 2007 edition.
- Factory Mutual Data Sheet 5-48, Automatic Fire Detection, Oct. 2021 edition.
- International Building Code (IBC), 2021 edition
- International Fire Code (IFC), 2021 edition
- NFPA 70 National Electrical Code, 2023 edition.
- NFPA 72 National Fire Alarm and Signaling Code, 2022 edition.
- NFPA 90A, Standard for the Installation of Air-Conditioning and Ventilating Systems, 2021 edition.
- NFPA 101 Life Safety Code, 2021 edition.
- NFPA 170 Standard for Fire Safety and Emergency Symbols, 2021 edition.
- Underwriters Laboratories (UL) Fire Protection Equipment Directory

Please note that this solicitation may result in material procurements and proposals greater than \$10,000 and must comply with FAR 52.225-11 Buy American Act – Construction Materials Under Trade Agreements (SEP 2010). If you cannot comply or foresee any issues with compliance, please provide a detailed explanation.

If your company is **interested** in this solicitation, please **proceed to Section 4.0** and complete the below sections as requested. The BNI Acquisition Services Purchasing group is responsible for collection, evaluation, and internal publication of potential bidders' information for the purpose of pre-qualification for all solicitations.

4.0 Response Submittal

4.1 Submission Due Date: 4/30/2025

Submission Method: Submissions must be received no later than the due date to the Purchasing Representative, Andrea Riste, via email at adriste@bechtel.us. For questions, call (509) 430-9055.

5.0 Pre-Selection Criteria

5.1 Company Response

Prime Subcontractor Company Name:	
Address:	
Pre-qualification Contact Name:	
Phone Number:	
E-mail Address:	
DUNS No. (Dun & Bradstreet):	

COMPANY NAME:	
---------------	--



5.2	North	North American Industry Classification System Code (NAICS)				
	stand	dard fo	or this code is 75		pre-qualification purpose	s work is 335314 . The SBA sizes, you are a small business if
					☐ Small	
	Business Size Classification (according to U.S. Small Business Administration Criteria)				☐ Small Disadvantaged Business	
				ion (according to	☐ Woman Owned Small Business	
					☐ HUBZone Business	
				,	☐ Veteran-Owned Sm	nall Business Concern
					☐ Service-Disabled V	eteran-Owned Small
					Business Concern.	
					☐ N/A – Registered as	s a Large Business
5.3	Qual	ity Ass	surance Require	ements Program		
	Prog	ramma	atic Quality Ass	urance (QA) require	ments for this purchase o	orders will be in accordance with
	Supp	lier Q	A program, plea	ase mark as applicab	ole:	
				Quality - Based on E	OOE Order 414.1C ASME NQA-1 2022	
	۸					-2
	A. Does your Company have a written Quality Assurance Program?				1?	
	□Yes □ No					
	B. Which QA standards does this program meet?					
	☐ DOE/RW/0333P ☐ ASME NQA-1 ☐ ASME Section VIII ☐ ISO-9000 ☐ Other					
	C. If selected "other" above, please furnish a copy of your QA Program Table of Contents and a brief summary identifying each of the requirements listed below. The level of rigor applied to the elements shall be commensurate with the risks associated with the Work.					
		 A description of the organizational structure, functional responsibilities, levels of authority and interfaces for those managing, performing, and assessing the Work. 				
		•	Personnel Tra	ining and Qualification	ons	
		•	Quality Improv	/ement		
		•	Control of Doo	cuments and Record	s	
		•	Work Process	es		
		•	Design			
		•	Procurement			
		•	Product Identi	fication and Traceab	ility	
		•	Inspection			and Acceptance Testing
				OFFICIAL USE ON	ILY (when completed)	

COMPANY NAME:	
---------------	--



- Control of the Testing Equipment
- Control of Non-Conforming Product
- Corrective and Preventative Actions
- Handling, Storage and Shipping Procedures
- Management Assessment
- Independent Assessment
- \Box Your company has the option to submit their full Quality Assurance Plan with this interest

_ 4	\sim		
5.4	Comm	arcial	I lata
J. T	COILLII	CIGIAI	Data

D .	rour company has the option to submit their fair Quality Assurance Figure with this interest.			
Comm	ercial l	Data		
		ders are required to register on the <u>Bechtel Supplier and Contractor Portal:</u> <u>Bechtel.com/supplier/</u> in order to be considered.		
Date y	our co	mpany registered or updated its information on the Portal?		
	Date	Updated:		
A.	Roug	gh Order of Magnitude for Scope of Work (USD): \$		
B.	Estin	nated Delivery Schedule:		
	i. ii. iii. iv.			
C.	Are t	here any long lead items to be aware of (if yes, please specify)?	_	
D. more o		s your company have a suggested alternate offering/product that offers an improvement, ifective, or offers shorter delivery (i.e. "buy what you make")?	is	
		No, we will supply an identical or similar product.		

5.5 **Technical Criteria**

mitigate?

E.

Direct Relevant Experience Documentation: If the Respondent has answered "yes" to the A. foregoing questions, provide a reference list of example projects over the last ten years, on the included Experience Statement, that demonstrate direct relevant project experience to support

What risks do you foresee with this procurement that BNI should be aware of and possibly help

OFFICIAL USE ONLY (when completed)

Yes, we have an alternate offering. If so, please provide.

COMPANY NAME:	
---------------	--



each "yes" response. Example projects should be detailed as to both the technical scope of the project and your participation in the project.

Column completion notes for the below, Experience Statement, to be completed by the Prime contractor:

- A. <u>Customer Name</u>, <u>Address</u>, <u>Contact Name and Phone No</u>.- So that we may contact as a reference as needed.
- B. Work Description and Location- Describe work scope and location, and then indicate if prime or subcontract.
- C. Original/Final Contract Value- Original award value and final closeout contract value.
- D. <u>Commencement/ Completion Dates</u>- Provide starting date and actual completion (or forecast if still in progress) by month/year format (e.g., Jan 2006/ Sept 2007)

Customer Name, Address, contact Name and Phone No.	Work Description and Location	Original/Final Contract Values	Commence/ Complete Dates
6.0 Pre-Qualification Doc	cument Checklist		

Companies are encouraged to use this checklist to ensure their submittal is complete.
☐ Interest & Prequalification Criteria and Response Package (this document)
☐ QA Program Table of Contents and summary <i>or</i> a copy of QA Plan

COMPANY NAME:	
---------------	--



☐ Additional supporting documentation such as brochures and company profiles.
☐ Direct Relevant Experience Documentation (included in this document or provided as attachment)

This page intentionally left blank.